

## Hangzhou Easy Electric Wire and Cable Co.,LTD

Add: Room 305, Building 2, No. 380 Fengxin Road, Hangzhou, China

www.eescable.com

## **TEST REPORT**

Products	ACSR		Size	Size 1/0AWG REVEN		
Standard	6+1/3.37	Invoice No.	20230107003	Date	2023.1.7	
NO.	Item	Standards and	Requirements	Test Results	Evaluation	
1	Structure					
1-1	Number Of AL Wire	6		6	Qualified	
1-2	Number Of Steel Wire	1		1	Qualified	
1-3	Diameter Of Conductor	10.11±10%		10.16	Qualified	
1-4	20℃ Max D.C Resistance	≤0.5232 Ω /km		0.5169	Qualified	
1-5	The direction of outer layer	Right- handed		Right- handed	Qualified	
2	Surface Of Conductor					
2-1	Surface Quality	The Surface Shall Be Smooth, Stranded Compactly, No Missing, Broken, Jumping or Loosing Strands.		Smooth Compact	Qualified	
3	Aluminum Wire Properties					
3-1	Material	Hard drawn a	aluminum wire	Hard drawn aluminum wire	Qualified	
3-2	Diameter Of AL Wire	6/3.37		6/3.37	Qualified	
3-3	Min. Tensile Strength	160N/mm2		175	Qualified	
3-4	Resistivity at 20℃	≤0.028264		0.027862	Qualified	
3-5	Elongation in 10 in	1.6%		2.4%	Qualified	
4	Steel Wire Properties					
4-1	Diameter Of Steel Wire	1/3	.37	1/3.37	Qualified	
	· — — — — — — — — — — — — — — — — — — —					

## Hangzhou Easy Electric Wire and Cable Co.,LTD

4-2	Min. Tensile Strength	1410N/mm2	1546	Qualified
4-3	Min.stress at 1% elongation	≥1310N/mm²	1382	Qualified
4-4	Elongation	≥3%	6%	Qualified

Tested by: Shaoqiong He

Checked by: Guohui Xu

杭州益睿电线电缆有限公司 BANGZHOU EASY ELECTRIC VIRE AND CABLE CO., LTD.