

12-220KV

Pin Composite Insulator



Type	Rated voltage (KV)	Specified mechanical load	Section length (mm)	Min Arc distance (mm)	Leakage distance (mm)	Lightning impulse withstand BIL(KV)	Power frequency withstand (wet) (KV)
FZSW-12/4	12	4	215	290	100/90	75	42
FZSW-24/8	24	8	400	750	142	150	65
FZSW-36/6	36	6	450	946	148/118	185	95
FZSW-66/6	66	6	760	1886	160/130	410	185
FZSW-66/8	66	8	760	2010	220/190	410	185
FZSW-110/10	110	10	1220	3530	220/190	500	230
FZSW-220/10	220	10	2440	7060	220/190	1000	395

12-220KV

Pin Composite Insulator



Type	Rated voltage (KV)	Specified mechanical load	Section length (mm)	Min Arc distance (mm)	Leakage distance (mm)	Lightning impulse withstand BIL(KV)	Power frequency withstand (wet) (KV)
FZSW-12/4	12	4	215	290	100/90	75	42
FZSW-24/8	24	8	400	750	142	150	65
FZSW-36/6	36	6	450	946	148/118	185	95
FZSW-66/6	66	6	760	1886	160/130	410	185
FZSW-66/8	66	8	760	2010	220/190	410	185
FZSW-110/10	110	10	1220	3530	220/190	500	230
FZSW-220/10	220	10	2440	7060	220/190	1000	395